

TECHNICAL DATA SHEET

OLD MASTERS[®] FURNITURE REFINISHER

AVAILABLE SIZES: Pint (08), Quart (04) and Gallon (01)

PRODUCT CODES: 00608 Pint

00604 Quart

00601 Gallon

PRODUCT DESCRIPTION: Old Masters[®] Furniture Refinisher is a fast-acting liquid finish remover. It quickly dissolves varnish, lacquer and shellac. This product will not destroy the patina or natural color of wood. It will not raise the grain or loosen glue joints, veneers, inlays, wood fillers or laminated woods. Furniture Refinisher is also effective as an after wash following paint removal.

This product is flammable, and as with all removers, we recommend the use of gloves, ample ventilation and normal caution when working near fire hazards, sparks, electrical receptacles or heat sources.

DIRECTIONS FOR USE: Before You Begin

- Read the entire label, its directions and cautions carefully.
- Use caution when opening can. Hold rag over cap until pressure is released.
- For best results, use when temperature is between 60° and 85°F. Apply away from strong breezes and hot sun.

To Apply

1. Pour a small amount of Furniture Refinisher into a wide mouth container. Dip a small piece of steel wool in the Refinisher. Squeeze out excess.
2. Gently rub the surface with the dampened steel wool. Work within a small area. As the old finish becomes tacky, rinse and squeeze steel wool in the work container. Continue until all tackiness and residue is removed from the working area.
3. Repeat on adjacent areas, overlapping each work area until the entire project is clean. Rub surface with long strokes following woodgrain. Use clean refinisher and steel wool. Buff with clean, dry steel wool or towel.
4. Allow surface to dry thoroughly. Apply finish coat when surface is completely dry and dust free. We recommend Old Masters[®] Tung Oil for a hand rubbed finish, or Old Masters[®] varnishes or polyurethanes for a protective finish.

MAX VOC: 816 g/L (6.8 lbs/gal)

TECHNICAL DATA SHEET

OLD MASTERS[®] FURNITURE REFINISHER

TECHNICAL DATA

SOLIDS BY WEIGHT:	Not applicable	FLASH POINT:	14°F Tag Closed Cup
SOLIDS BY VOLUME:	Not applicable	VISCOSITY AT 77 °:	14 sec. #2 Zahn Cup
V.O.C.:	816 grams/liter	AVERAGE DRY TIME @ 70°F AND 50% R.H.:	Not applicable
THEORETICAL COVERAGE @ Mil DFT:	Not applicable	VEHICLE:	Mineral spirits
COVERAGE @ RECOMMENDED DFT	Not Applicable	RECOMMENDED THINNER:	Do no thin. Use as packaged.
RECOMMENDED DFT PER COAT:	Not Applicable		
WEIGHT PER GALLON:	7.60 lbs		

Limited Warranty Since Old Masters[®] does not control the application of its products, nor is the condition of the surface to which they are applied, a Limited Warranty provided. If the products do not perform as specified, for whatever reason, Old Masters[®] liability will under no circumstances exceed the replacement of the product.