

M A T E R I A L S A F E T Y D A T A S H E E T

I. IDENTIFICATION

MANUFACTURED BY: Old Masters
303 19th St SE
Orange City, IA 51041

REVISED: 04/21/2011
PRINTED: 04/22/2011

24 Hour Emergency Telephone
CHEMTREC 1-800-424-9300

General Information:
Mon-Fri 8 AM - 5 PM
712-737-4993

TRADE NAME: OM BRUSHING LACQUER SEMI-GLOSS AEROSOL

MFG. PRODUCT NUMBER: 92810

II. HAZARDOUS INGREDIENTS

CAS #78-93-3	Methyl Ethyl Ketone	WT %: 20-50	Footnote: (1)
	ACGIH TLV: 200 ppm TWA	ACGIH STEL: 300 ppm	
	OSHA PEL: 200 ppm TWA	OSHA CEILING:	OSHA PEAK:
	VAPOR PRESSURE: 83mm Hg75F	LEL%: 1.8	
CAS #75-28-5	Isobutane	WT %: 5-20	Footnote: (1)
	ACGIH TLV: N.E.	ACGIH STEL:	
	OSHA PEL: N.E.	OSHA CEILING:	OSHA PEAK:
	VAPOR PRESSURE: 3.1 atm	LEL%: 1.6	
CAS #74-98-6	Propane	WT %: 5-20	
	ACGIH TLV: 2500 ppm TWA	ACGIH STEL:	
	OSHA PEL: 1000 ppm TWA	OSHA CEILING:	OSHA PEAK:
	VAPOR PRESSURE: 7150mmHg20c	LEL%:	
CAS #110-43-0	Methyl Amyl Ketone	WT %: 5-20	Footnote: (1)
	ACGIH TLV: 50 PPM TWA	ACGIH STEL:	
	OSHA PEL: 100 ppm TWA	OSHA CEILING:	OSHA PEAK:
	VAPOR PRESSURE: 2.14 mm	LEL%: 1.1	
CAS #108-10-1	Methyl Isobutyl Ketone	WT %: 5-20	Footnote: (1)
	ACGIH TLV: 50 ppm TWA	ACGIH STEL: 75 ppm	
	OSHA PEL: 100 ppm TWA	OSHA CEILING:	OSHA PEAK:
	VAPOR PRESSURE: 15mm Hg20C	LEL%: 1.2	
CAS #71-36-3	n-Butanol	WT %: 5-20	Footnote: (1)
	ACGIH TLV: 50 ppm SKIN	ACGIH STEL: 150 ppm SKIN	
	OSHA PEL: 100 ppm TWA	OSHA CEILING: 150 mg/m3 SKIN	OSHA PEAK:
	VAPOR PRESSURE: 4.4 mm	LEL%: 1.45	
CAS #1330-20-7	Xylene	WT %: 5-20	Footnote: (1)
	ACGIH TLV: 100 ppm	ACGIH STEL: 150 ppm	
	OSHA PEL: 100 ppm	OSHA CEILING: NE	OSHA PEAK: NE
	VAPOR PRESSURE: 7 mmHg@20C	LEL%: 1	
CAS #97-85-8	Isobutyl Isobutyrate (IBIB)	WT %: 1-5	
	ACGIH TLV:	ACGIH STEL:	
	OSHA PEL:	OSHA CEILING:	OSHA PEAK:
	VAPOR PRESSURE:	LEL%:	
CAS #112-34-5	Diethylene Glycol Butyl Ether	WT %: 1-5	Footnote: (1)
	ACGIH TLV: N.E.	ACGIH STEL:	
	OSHA PEL:	OSHA CEILING:	OSHA PEAK:

Material will float and may ignite on surface of water. Use water spray to keep fire exposed containers cool. Water may be ineffective in fighting the fire.

V. HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: See Section II.

EFFECTS OF OVEREXPOSURE:

Inhalation - Anesthetic

Irritation of the respiratory tract or acute nervous system. Depression characterized by headache, dizziness, staggering gait, confusion, unconsciousness or coma.

Acute - High vapor concentrations are irritating to the eyes and the respiratory tract, and may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects including death. Product has a low order of acute oral and dermal toxicity, but minute amounts aspirated into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possible death.

Chronic - Xylene contains ethylbenzene which has been classified as a possible carcinogen to humans, Group 2B, by the International Agency for Research on Cancer (IARC), based on sufficient evidence in laboratory animals but inadequate evidence for cancer in humans. Prolonged or repeated overexposure to ethylbenzene may cause the following effects: kidney effects, liver effects, lung effects, thyroid effects, testicular effects, pituitary effects.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: consult physician

PRIMARY ROUTE(S) OF ENTRY: Skin and Inhalation

EMERGENCY AND FIRST AID PROCEDURES: Inhalation - Remove to fresh air.
Eyes - Flush immediately with fresh water for 15 minutes.
Call a physician.
Skin- Wash thoroughly with soap and water

VI. REACTIVITY DATA

STABILITY: *stable*

HAZARDOUS POLYMERIZATION: *will not occur*

INCOMPATIBILITY: Strong oxidizing agents, strong reducing agents, strong acids, strong alkalis

HAZARDOUS DECOMPOSITION: When heated to decomposition, toxic fumes are formed.

CONDITIONS TO AVOID: Fire, burning, and welding.

VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition (flames, hot surfaces and electrical, static or frictional sparks). Avoid breathing vapors. Ventilate area. Use non-sparking tools. Remove with inert absorbant.

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. Do not incinerate closed containers.

VIII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: For casual use none required. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA approved) or leave the area. Avoid contact with eyes, skin and clothing.

VENTILATION: Provide general dilution or local exhaust ventilation in volume and pattern to keep TLV and LEL of most hazardous ingredient in Section II, below acceptable limit.

PROTECTIVE GLOVES: None required except for prolonged contact.

EYE PROTECTION:

Splash proof eye goggles. In emergency situations, use eye goggles with a full face shield.

OTHER PROTECTIVE EQUIPMENT: *none*

HYGIENIC PRACTICES: See Section V

IX. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Do not store above 120 degrees F. Store large quantities in buildings designed and protected for storage of NFPA Class 1A flammable liquids.

OTHER PRECAUTIONS: Do not spray in eyes. Do not puncture or incinerate cans. Do not stick pin or any sharp objects into opening on top of can. Finger must not protrude over spray button.

92810

5

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants':

Ingredient	CAS #	Wt% of HAPS in product	Pounds HAPS/ Gal product
-----	-----	-----	-----
Xylene	1330-20-7	5.9 %	0.4
Methyl Isobutyl Ketone	108-10-1	5.3 %	0.3
Diethylene Glycol Butyl Ether	112-34-5	2.1 %	0.1
